

INFINITY Spray Plaster



Introducing Infinity Spray Plaster:

Infinity Spray Plaster is a ready-to-use, airless spray-applied plaster designed for interior levelling and fine finishing of walls and ceilings.



SUITABLE SUBSTRATES

Infinity Spray Plaster can be applied to both new and renovated substrates, whether painted or unpainted, including:

- Gypsum
- Plasterboard / drywall
- Old painted surfaces
- Cement
- Concrete
- Cellular concrete

No primer or sealer is required before application.

OVERCOATING

Once dry, Infinity Spray Plaster can be overcoated with all types of fillers, paints, or wall coverings.

Key Benefits

PHYSICAL & TECHNICAL CHARACTERISTICS

- Ready-to-use airless spray plaster formulated with mineral components and synthetic resin
- Characterisation (NFT 36-005): Family III – Class 2
- Codification (EN 16566): G3S1V0W0A0C0R0
- Mixing: Ready to use, no dilution required
- Recommended application thickness: Up to 5 mm
- Coverage: Approx. 1.7 kg/m²/mm
- Setting time: Second coat may be applied once the first coat is hard and dry to the touch
- Overcoating: Paintable after 24–48 hours (once completely dry)
- Colour: White

USE & STORAGE CONDITIONS

• Application tools: Any airless spray machine with a minimum flow rate of 5 L/min.

Recommended nozzles: 5.31, 5.35, 6.31, 6.35

• Cleaning: Clean tools immediately with water

• Storage:

– Store in original sealed packaging

– Keep away from frost and direct sunlight

PACKAGING

- 20 kg buckets

RECOMMENDATIONS & APPLICATION GUIDANCE

- All times provided are indicative and depend on substrate type, coat thickness, temperature, and humidity
- Do not apply when:
 - Temperature is below 8°C or above 35°C
 - Relative humidity exceeds 70%
 - Substrates are damp or overheated
- Not suitable for application on polystyrene, wallpaper, or exterior surfaces

SUBSTRATE PREPARATION

Prepare substrates according to standard trade practices. Surfaces must be hard, cohesive, clean, sound, and dry.



Infinity Spray Plaster - Specification

Type	All In One Spray Plaster (No-VOC)
Mix ratio	Pre-Mixed - add DI water if necessary
Pack Sizes	20KG Buckets
Colour	White
Shelf Life & Storage	8 months in original, unopened container. Store in cool, dry conditions