

COMPARISON WALLS

	IE Spray Stone	Exterior Wall Paint	Pebble Dashing	Render	Stucco
Non Fade	✓	✓	✗	✗	✓
Anti Cracking	✓	✗	✗	✗	✗
No Overlapping	✓	✗	✗	✗	✗
Anti-Bacterial	✓	✓ / ✗	✗	✗	✗
Eco - Friendly	✓	✓ / ✗	✗	✗	✓ / ✗
Low Material Wastage	✓	✓	✗	✗	✗
Easy Application	✓	✓	✓	✗	✗
Easy Maintained, Cleaned	✓	✓	✗	✗	✗
Choice Of Texture	✓	✗	✗	✓	✗
Notes:	10 - year service guaranteed (Recoating & Patch Repair Simple)	2 - 5 year service life. (Paint Peels & Flakes Over-Time, Requires Recoating Often)	10 - year service Pebble dash loses waterproofing qualities quickly leading to cracks.	Plaster is mainly weak in tension & flexural strength, liable to cracking. High material Wastage.	Stucco can not be recoated & must be shotblasted off before recoat. Labour intensive installation.



SPRAY STONE ADVANTAGES



High Water Retention



Natural Granite Effect



Anti-Cracking Properties



No Overlapping Defects



Environmentally Friendly



Low Wastage Of Material



Easy Application



Long Service Life



Anti - Bacterial

Infinity Effects Spray Stone V2



Introducing our revolutionary Spray Stone V2 System, a highly advanced solution for stone coatings. Working with our Spray Stone V2 machine, the system delivers superior flexibility and adaptability compared to traditional methods. Say goodbye to surface cracking and weakened structural integrity.

Our Spray Stone V2 system is incredibly versatile, suitable for a wide range of surfaces and applications. Enhance the appearance of exterior or interior walls, industrial flooring, decorative flooring, metal beams, plastic PVC gutters, kitchen countertops, doors, or timber fencing with ease. Enjoy exceptional durability and hardness now improved even further. With our new Thixx Additive, the system is not only sprayable but also fully trowelable.

Our Spray Stone V2 is more than just a coating. It dries quickly, has no odor, and is safe for the environment. Achieve realistic stone effects with a wide range of color options, now available in 1000+ colours. It is resistant to mold, mildew, alkali, water, UV rays, weather conditions, and chemicals. It also offers excellent fire resistance.

Our coating is washable, resistant to scuffs, non-fading, and highly durable. Enjoy easy application, extensive coverage, and minimal maintenance. Unlike real stone or traditional ceramic, our Spray Stone V2 system eliminates safety concerns.

COMPARISON FLOORING

	IE Spray Stone	Epoxy Flake Flooring	Epoxy Floor Paint	Concrete	Polished Concrete	Decorative Epoxy Resin flooring
UV Stable	✓	✗	✗	✗	✗	✓
Chemical Resistant	✓	✓	✓	✗	✓	✓
Stain Resistant	✓	✓	✗	✗	✓	✓
Anti-Bacterial	✓	✓	✓ / ✗	✗	✗	✓
Anti-Slip	✓	✓	✓ / ✗	✗	✗	✓ / ✗
High Scuff Resistance	✓	✓	✓	✗	✓	✓
Easy Application	✓	✓	✓	✗	✗	✗
Easy Maintained, Cleaned	✓	✓	✓	✗	✓	✓
Choice Of Texture	✓	✗	✗	✗	✗	✓
Notes:	1/2 Day Install, Quick Dry Time, Full Cure 3 Days,	1-2 Day Install, Full Cure 7-14 Days, More Steps Required To Complete	Rolled on usually 1-2 Part System (Paint peels & flakes overtime recoat often needed)	Weathering quickly leads to cracks & damp. Staining occurs easily	Hard coating will crack if any movement, Cold underfoot. If not sealed penetration by moisture can lead to growth of mold or mildew.	Long prep and install process 3-7 days, can be a nightmare if not installed correctly by professional. Even professional floors discolour fast and have small defects.

Order your Infinity Effects Spray Stone V2: directly from Infinity Effects or through our global distribution agents. Please note that all Infinity Effects products are sold according to our Standard Conditions of Sale. While we aim to provide helpful advice, we can only guarantee results for uses explicitly confirmed in writing by Infinity Effects and the specified representative.



Infinity Effects Spray Stone V2

INFINITY
EFFECTS[®]

Introducing Infinity Effects Spray Stone V2



Introducing Spray Stone V2

The next evolution of our industry-leading stone effect system. Engineered with upgraded chemistry, **V2 now delivers increased adhesion, improved durability, and enhanced versatility across almost any surface.**

Now available with **all new colour codes**, Spray Stone V2 offers a wide design range with incredibly realistic stone finishes. Whether you are coating:

- ✓ Internal / External Walls
- ✓ Floors,
- ✓ Metals,
- ✓ PVC, UPVC, Plastic
- ✓ Timber,
- ✓ Furniture
- ✓ Architectural features,

V2 provides a seamless and **extremely durable stone effect** with minimal maintenance.

With our breakthrough **Infinity Thixx Additive**, you can now trowel the system onto horizontal or vertical surfaces, creating application possibilities never before achievable with spray-applied stone systems.

Spray Stone V2 is fast-drying, odour-free, non-toxic and formulated using our eco-driven coating technology. The system is waterproof, UV-resistant, anti-fungal, alkali-resistant, chemical-resistant, non-fading and built for long-term performance in harsh environments.

Infinity have created stone systems for everything imaginable, and **V2 advances this even further.**

For ordering, colour codes or distributor information, contact Infinity Effects or your authorised supplier. All products are supplied under our Standard Conditions of Sale.



Infinity Effects Spray Stone V2

INFINITY
EFFECTS[®]

TECHNICAL PARAMETERS

Property	Solvent free (Water based)
Dry film thickness	3mm per layer dependent
Coverage	Dependent on desired finish
Drying time (surface dry)	>8h (25-27°C) (77 - 81°F)
Touch dry	<4h (25-27°C) (77 - 81°F)
Drying time (complete)	>24h (25-27°C) (77 - 81°F)
Coating layer	2-3 layers
Service life	> 10 years (Walls)
Paint colors	Stone catalog / Fan Book
Application way	Spray gun / Trowel
Storage	<30°C, °F cool, dry



Infinity Effects Spray Stone V2



Infinity Effects Spray Stone V2 Colour Chart



MORE COLOURS AVAILABLE OVE 1000+ CONTACT REPRESENTIVE



DISCLAIMER: Customers are advised to thoroughly read and adhere to the instructions provided to ensure the optimum finish and performance of our products. The information presented is based on results gained from experience and tests and is believed to be accurate. However, we do not accept liability for any loss or damage attributable to reliance on this information, as conditions of use may lie outside our control. Any deviation by the user from these instructions may affect the performance of the products, and therefore, such actions are not advised. In such circumstances, Infinity Effects will not be held responsible.

Users should always conduct sufficient tests to establish the suitability of any products for their intended applications. While we strive to ensure consistency of color in production, slight variations in shade may occur from batch to batch.

Note: If you are unsure about the compatibility of Infinity Effects Coating with the substrate surface, we strongly recommend conducting a small test in a discreet area before applying it to the entire floor. This precaution will help ensure a successful and satisfactory outcome.



Infinity Effects Spray Stone V2

INFINITY
EFFECTS®

